

Shenzhen BaoBao Industrial Co., Ltd

Leading Manufacturer and Supplier
of Touch Screen Devices



- POS System
- Industrial Panel PCs
- Touch Screen Monitors
- Stretched Bar LCD Displays
- Open Frame Touch Screen Monitors
- Slot Machine Touch Screen Monitors

ZULJANA

☎ +86 769 81009070

☎ +86 769 81009071

✉ enquiry@baobao-industries.com

🌐 www.baobao-industries.com

ABOUT US

Shenzhen BaoBao Industrial Co., Ltd specializes in the design, development, manufacturing and marketing of Touch screen monitor, Industrial panel pc, Self-Service Kiosk, Pos system, Digital Signage, Stretched Bar LCD Displays, Slot Machine Touch Screen Monitors, ODM and OEM Projects. With its roots in China, BaoBao Industrial today sells and supports Touch Devices on a worldwide basis. BaoBao Industrial offers German engineered products, manufactured in Asia with local service. We are founded in 2014 located in Shenzhen China.

BaoBao Industrial have powerful technology Advantage and regress quality control process and have already got certifications of CE FCC ROHS CCC IP65 HDMI. BaoBao Industrial has won favor of many customers from all over the world such as North America, South America, Eastern Europe, western Europe, Australia South East Asia and Middle East. BaoBao Industrial is famous for professional product performance, high quality and cost effective.



CORE TECHNOLOGY





HONORS

CERTIFICATE OF COMPLIANCE

NTEK 北测

Supplier's Declaration of Conformity
According to FCC part 15
Ref. No. 221648070187

Product: Touch Screen Monitor
Trade Mark: Zujin
Applicant: Shenzhen Baobao Industrial Co., Ltd.
Address: 2/F, Building B, Xinhongcheng Science and Technology Park, No. 5-1, Lanting Industrial City, Shanghai, Gonggang Town, Guangdong, New District, Shanghai
Manufacturer: Shenzhen Baobao Industrial Co., Ltd.
Address: 2/F, Building B, Xinhongcheng Science and Technology Park, No. 5-1, Lanting Industrial City, Shanghai, Gonggang Town, Guangdong, New District, Shanghai
Factory: Shenzhen Baobao Industrial Co., Ltd.
Address: 2/F, Building B, Xinhongcheng Science and Technology Park, No. 5-1, Lanting Industrial City, Shanghai, Gonggang Town, Guangdong, New District, Shanghai
Model: ZL17M, ZL15T17MBCAP, ZL15T15MBCAP, ZL15T17MBCAP, ZL15T15MBCAP, ZL15T17MBCAP, ZL15T15MBCAP, ZL15T17MBCAP, ZL15T15MBCAP, ZL15T17MBCAP

The test sample of product has passed the test according to requirements of the following standards:
Standard(s): FCC Part 15, Subpart B, 15.1-15.242
Test report(s) No.: 221648070187

ROHS Approved by Client: [Signature]
Department Manager: [Signature]

Shenzhen NTEK Testing Technology Co., Ltd.
Address: 15 Building B, Xinhongcheng Science and Technology Park, No. 5-1, Lanting Industrial City, Shanghai, Gonggang Town, Guangdong, New District, Shanghai
Tel: 0086-755-22164807 0226-3288 2022-2024 Website: www.ntek.org.cn

Certificate CN2300005667

The management system of **Shenzhen Baobao Industrial Co., Ltd.**

ISO 9001:2015

has been assessed and certified according to requirements of ISO 9001:2015

For the following product:
Design and manufacture of touch display, in-built touch kit and touch controller, PCB assembly and touch interface module

The certificate is valid from 01 February 2023 until 01 February 2026 unless notified by a conformity assessment body.

Next 1: Certificate issue 01 February 2023

[Signature]

SGS IAF

Certificato di esame UE del tipo EU-type examination certificate
n. ECM 21 ATEX-B UD37

Motivato in forza della direttiva 2014/53/CE - Allegato II - Articolo 8
con riferimento ai 19158343 (000001 - 000002) - 000003

Ex **ECM**

Applicant: Shenzhen Baobao Industrial Co., Ltd.
Address: 2/F, Building B, Xinhongcheng Science and Technology Park, No. 5-1, Lanting Industrial City, Shanghai, Gonggang Town, Guangdong, New District, Shanghai
Product: Touch Screen Monitor
Model: ZL17M, ZL15T17MBCAP, ZL15T15MBCAP, ZL15T17MBCAP, ZL15T15MBCAP, ZL15T17MBCAP, ZL15T15MBCAP, ZL15T17MBCAP, ZL15T15MBCAP, ZL15T17MBCAP

The certificate is valid from 01 February 2023 until 01 February 2026 unless notified by a conformity assessment body.

Next 1: Certificate issue 01 February 2023

[Signature]

Ente Certificazione Macchine srl

CERTIFICATE OF COMPLIANCE

NTEK 北测

CERTIFICATE OF ROHS COMPLIANCE
According to Directive 2011/65/EU
Ref. No. 221648070187

Product: Touch Screen Monitor
Trade Mark: Zujin
Applicant: Shenzhen Baobao Industrial Co., Ltd.
Address: 2/F, Building B, Xinhongcheng Science and Technology Park, No. 5-1, Lanting Industrial City, Shanghai, Gonggang Town, Guangdong, New District, Shanghai
Manufacturer: Shenzhen Baobao Industrial Co., Ltd.
Address: 2/F, Building B, Xinhongcheng Science and Technology Park, No. 5-1, Lanting Industrial City, Shanghai, Gonggang Town, Guangdong, New District, Shanghai
Factory: Shenzhen Baobao Industrial Co., Ltd.
Address: 2/F, Building B, Xinhongcheng Science and Technology Park, No. 5-1, Lanting Industrial City, Shanghai, Gonggang Town, Guangdong, New District, Shanghai
Model: ZL17M, ZL15T17MBCAP, ZL15T15MBCAP, ZL15T17MBCAP, ZL15T15MBCAP, ZL15T17MBCAP, ZL15T15MBCAP, ZL15T17MBCAP, ZL15T15MBCAP, ZL15T17MBCAP

The test sample of product has passed the test according to requirements of the following standards:
Standard(s): RoHS (EU) 2011/65/EU
Test report(s) No.: 221648070187

ROHS Approved by Client: [Signature]
Department Manager: [Signature]

Shenzhen NTEK Testing Technology Co., Ltd.
Address: 15 Building B, Xinhongcheng Science and Technology Park, No. 5-1, Lanting Industrial City, Shanghai, Gonggang Town, Guangdong, New District, Shanghai
Tel: 0086-755-22164807 0226-3288 2022-2024 Website: www.ntek.org.cn

CERTIFICATE OF COMPLIANCE

NTEK 北测

CERTIFICATE OF EMC COMPLIANCE
According to Directive 2014/53/EU
Ref. No. 221648070187

Product: Touch Screen Monitor
Trade Mark: Zujin
Applicant: Shenzhen Baobao Industrial Co., Ltd.
Address: 2/F, Building B, Xinhongcheng Science and Technology Park, No. 5-1, Lanting Industrial City, Shanghai, Gonggang Town, Guangdong, New District, Shanghai
Manufacturer: Shenzhen Baobao Industrial Co., Ltd.
Address: 2/F, Building B, Xinhongcheng Science and Technology Park, No. 5-1, Lanting Industrial City, Shanghai, Gonggang Town, Guangdong, New District, Shanghai
Factory: Shenzhen Baobao Industrial Co., Ltd.
Address: 2/F, Building B, Xinhongcheng Science and Technology Park, No. 5-1, Lanting Industrial City, Shanghai, Gonggang Town, Guangdong, New District, Shanghai
Model: ZL17M, ZL15T17MBCAP, ZL15T15MBCAP, ZL15T17MBCAP, ZL15T15MBCAP, ZL15T17MBCAP, ZL15T15MBCAP, ZL15T17MBCAP, ZL15T15MBCAP, ZL15T17MBCAP

The test sample of product has passed the test according to requirements of the following standards:
Standard(s): EMC 2014/53/EU
Test report(s) No.: 221648070187

CE Approved by Client: [Signature]
Department Manager: [Signature]

Shenzhen NTEK Testing Technology Co., Ltd.
Address: 15 Building B, Xinhongcheng Science and Technology Park, No. 5-1, Lanting Industrial City, Shanghai, Gonggang Town, Guangdong, New District, Shanghai
Tel: 0086-755-22164807 0226-3288 2022-2024 Website: www.ntek.org.cn

APPLICATION

Due to our leading role in the consumer display market, Zuljana has broad experience adapting high-end touch technologies to the special display needs of the industrial display market.



Medical



HMI



POS



Queue Management



ATM



Self Service Kiosks



Ticket Management



Smart Table



Industrial



Aviation



Shelf Display





Advertisement

PCAPTOUCH

Zuljana provides factory designed and integrated touch panels with the touch controller included. Due to our in-house design and manufacturing capabilities, we are able to offer high quality, integrated PCAP solutions direct from our factory.

FEATURES:

- High reliability
- Suitable for a wide range of applications
- One stop solution






BETTER SERVICE


| Touch Controller

Zuljana cooperates with all major touch controller IC suppliers to individually select the best chip, so that the best possible compatibility between sensor and operating system and the optimal feature-set for your application is ensured. Zuljana customizes the tuning parameters and helps you with the integration on site through the local customer support.



| Cover Glass

The cover glass is the face of your product and thus a major part of brand identification. At Zuljana, the customer has every imaginable option to design his cover glass according to his personal specifications: material, decoration printing, logos, different shapes and surface treatments. Zuljana is maintaining good business relations with various glass manufacturers and can advise, arrange and manage to find the best overall solution. Together with the bonding and LCD, everything is carefully fine-tuned, and all come from a single source.






ADVANCED TECHNOLOGIES

Optical Bonding Technology

With optical bonding technology the TFT LCD module and PCAP-sensor are bonded together using an optical transparent adhesive. As a result the display readability is better than that of traditional frame bonding which leaves an air gap between TFT LCD surface and sensor glass.

FEATURES:

- Reduced reflection from the sun
- Isolation of water vapor and air
- Improved reliability and mechanical strength (vandalism proof)



Wet & Glove Technology

Wet & Glove PCAP displays perform even when the screen is wet and the operator is wearing gloves. For instance, by tuning the controller, the touch screen can be operated when a medical technician is using medical gels on the surface of the screen, or when an industrial operator is wearing gloves. With this technology, our PCAP touch panels support high end display devices used in challenging conditions such as construction, marine or medical applications.

It is relatively easy to detect a single touch point using our Wet & Glove technology. Two points can be simultaneously detected and the device controlled by gestures such as stretching or squeezing.



TED Technology

Touch Embedded Display (TED) technology integrates a high performance touch function sensor inside the TFT glass cell. TED creates a high quality liquid crystal display with good optical performance, good touch performance, in one display. The technology also achieves an ultra-narrow border design and slim module design. All these characteristics allow the final product designer greater design flexibility and results in an enhanced user experience.

FEATURES:

- High transmittance
- Super slim & lightweight
- Narrow border



On-cell Touch Technology

ITO pattern forms mutual capacitance electrodes on the color filter.

FEATURES:

- Tx & Rx form embedded structures on the TFT side
- One IC & one FPC drive the display and the touch panel simultaneously
- Ultra-low surface reflection
- Ultra-narrow bezel, ultra thin
- Very sensitive touch




Force Touch Technology

Force Touch is a new touch sensing technology. With this technology, the sensor can distinguish between various levels of force to accommodate different corresponding functions. This provides a better and more interactive experience for the users.

FEATURES:

- Stable and reliable structure
- Allows to distinguish many different force levels
- Can be combined with various touch technologies




Hover Touch Technology



Hover Touch is a brand-new touch sensing technology. Through hover touch, the operation can be accomplished without touching the screen.

FEATURES:

- Utilizes electrical for touch sensing of the user's finger
- The touch distance can reach 50mm



- Integration of touch control technology and display technology. Support multiple TFT module structures.



Active/Passive Stylus Pen Technology


The Active/Passive Stylus Pen Technology for LCDs allows users to write directly on the the LCD screen surface of a computing device such as a smartphone, tablet computer or Ultrabook. The Active/Passive Stylus Pen technology supports inductive capability for active pens, movable pens, electro-magnetic pens and resistance pens.

Multimodal Tactile Feedback

Tactile Feedback enables users to reconstruct the tactile sensation from a series of actions including force, vibration, and other Tactile commands.

FEATURES:

- Improves safety: Users can operate touch screen without looking at it!
- Improves operation: Users are able to identify which area on a display the image is shown, both visually and through tactile sensation to improve work efficiency.
- Improves sense of reality: Visual image combined with tactile feedback creates realistic experience.



- Texture sensation
- Click sensation

POS System

The Next POS Generation is Here

The touch screen POS system is designed to be reliable and high-performing. It works seamlessly with Android, Windows, and Linux, providing an easy-to-use experience. It ensures smooth and accurate transactions, equipping businesses with the necessary tools to succeed in a competitive market.



POS System



ZLX101POS	
Product Name	15.6" Touch Screen POS System
Model Number	ZLX101POS - ZLX101POS-1
Operating Display	15.6" Bezel Less TFT Display Aspect Ratio: 16:9 Capacitive Touch Screen Resolution: 1920 x 1080px
Second Display	10.1" TFT LCD VFD, 20 Columns x 2 Lines (Optional)
Operating System	Windows 11 / Android 11
Working Memory	4GB to 8GB
System Memory	32, 64, 128, 256 GB SSD
CPU	Intel® Celeron® J4125 RockChip RK3566
Other Peripherals	MSR Reader Wi-Fi® 802.11a/b/g/n/ac
Operating Temp	-10 °C ~ 60 °C 10% to 90% Humidity



ZLX102POS	
Product Name	15.6" Windows POS System
Model Number	ZLX102POS-W - ZLX102POS-A
Operating Display	15.6" TFT-Display Aspect Ratio: 16:9 Capacitive Touch Screen Resolution: 1920 x 1080
Second Display	Built-in 11.6" Second Display
Operating System	Windows 10 Pro / Android 11
Working Memory	4GB to 8GB
System Memory	16 to 256 GB SSD
CPU	Intel® Celeron® J4125 RockChip RK3566
Camera	Built-in
Operating Temp	-20 °C ~ 60 °C 10% to 90% Humidity



ZIPOS

Z1 Handheld POS System With Printer

This Handheld Mobile POS System is designed with an intelligent Cortex A53 Architecture and a powerful 11nm processor for optimal performance. It helps meet increased sales and ordering demands with lightning-fast execution.



ZLX107POSSL	
Product Name	15.6" Touch Screen POS Scale
Model Number	ZLX107POSSL
Operating Display	15.6" IPS Display Aspect Ratio: 16:9 Capacitive Touch Screen Resolution: 1920 x 1080
Second Display	10.1" TFT LCD VFD Customer Display
CPU	Intel® Celeron® J4125 RockChip RK3566
Operating System	Windows 10, Android 11
Working Memory	2 GB / 8 GB
System Memory	16, 64, 128, 256 GB SSD
Other Peripherals	Barcode Scanner High-speed 58/80mm Thermal Printer
Operating Temp	-20 °C ~ 60 °C 10% to 90% Humidity



ZLX106POS	
Product Name	11.6" Mini POS System
Model Number	ZLX106POS-W - ZLX106POS-A
Operating Display	11.6" TFT-Display Aspect Ratio: 16:9 Capacitive Touch Screen Resolution: 1366 x 768
Second Display	VFD, 20 Columns x 2 Lines (Optional)
CPU	Intel® Celeron® J4125 RockChip RK3566
Operating System	Windows 10 / Android 11
Working Memory	2 GB / 8 GB
System Memory	16, 32, 64, 128, 256 GB SSD
Other Peripherals	58/80mm Thermal Printer VFD Customer Display - Barcode Scanner Wi-Fi 2.4G/802.11 a/b/g/n Bluetooth 4.0/4.2 - NFC Reader (Optional)
Operating Temp	-20 °C ~ 80 °C 10% to 90% Humidity

Industrial Touch Screen Monitor

The Perfect Solution For Harsh Environments

Our industrial touch screen monitors are highly versatile and rugged, making them perfect for a wide range of applications. Whether it's factories, warehouses, or commercial settings, our monitors excel in delivering optimal performance.



Standard Sizes 7" - 55"

Industrial Touch Screen Monitor



ZL07TMBCAP

Product Name	7" Capacitive Touch Screen Monitor
Model Number	ZL07TMBCAP
IP rating	IP65 Front / IP40 Back
Active Display	15.36(H)×9.00(W)cm
Aspect ratio	16:9
Physical resolution	1024 × 600/1920 x 1080
Brightness	300(cd/m ²)
Contrast	700:1
Backlight Lifetime (hours)	LED/20,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL08TMBCAP

Product Name	8" Capacitive Touch Screen Monitor
Model Number	ZL08TMBCAP
IP rating	IP65 Front / IP40 Back
Active Display	16.31(H) × 12.25(W)cm
Aspect ratio	4:3
Physical resolution	1024 × 768
Brightness	300(cd/m ²)
Contrast	700:1
Backlight Lifetime (hours)	LED/20,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In




ZL97TMBCAP

Product Name	10" Capacitive Touch Screen Monitor
Model Number	ZL97TMBCAP
IP rating	IP65 Front / IP40 Back
Active Display	19.65(H) × 14.80(W)cm
Aspect ratio	4:3
Physical resolution	1024 × 768
Brightness	300(cd/m ²)
Contrast	800:1
Backlight Lifetime (hours)	LED/20,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In




ZL10ITMBCAP

Product Name	10.1" Capacitive Touch Screen Monitor
Model Number	ZL10ITMBCAP
IP rating	IP65 Front / IP40 Back
Active Display	21.80(H) × 13.66(W)cm
Aspect ratio	16:10
Physical resolution	1280×800
Brightness	300(cd/m ²)
Contrast	700:1
Backlight Lifetime (hours)	LED/20,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL104TMBCAP

Product Name	10.4" Capacitive Touch Screen Monitor
Model Number	ZL104TMBCAP
IP rating	IP65 Front / IP40 Back
Active Display	21.30(H) × 16.30(W)cm
Aspect ratio	4:3
Physical resolution	1024×768
Brightness	300(cd/m ²)
Contrast	700:1
Backlight Lifetime (hours)	LED/20,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL12ITMBCAP

Product Name	12.1" Capacitive Touch Screen Monitor
Model Number	ZL12ITMBCAP
IP rating	IP65 Front / IP40 Back
Active Display	24.60(H) × 18.40(W)cm
Aspect ratio	4:3
Physical resolution	1024 × 768
Brightness	300(cd/m ²)
Contrast	700:1
Backlight Lifetime (hours)	LED/20,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In

Industrial Touch Screen Monitor



ZL133TMBCAP

Product Name	13.3" Capacitive Touch Screen Monitor
Model Number	ZL133TMBCAP
IP rating	IP65 Front / IP40 Back
Active Display	29.5(H) × 16.70(W)cm
Aspect ratio	16:9
Physical resolution	1920×1080
Brightness	300(cd/m ²)
Contrast	700:1
Backlight Lifetime (hours)	LED/15,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL15TMBCAP

Product Name	15" Capacitive Touch Screen Monitor
Model Number	ZL15TMBCAP
IP rating	IP65 Front / IP40 Back
Active Display	30.40(H) × 22.80(W)cm
Aspect ratio	4:3
Physical resolution	1024×768
Brightness	300(cd/m ²)
Contrast	700:1
Backlight Lifetime (hours)	LED/30,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL156TMBCAP

Product Name	15.6" Capacitive Touch Screen Monitor
Model Number	ZL156TMBCAP
IP rating	IP65 Front / IP40 Back
Active Display	34.53(H) × 19.46(W)cm
Aspect ratio	16:9
Physical resolution	1920 × 1080
Brightness	300(cd/m ²)
Contrast	800:1
Backlight Lifetime (hours)	LED/15,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL17TMBCAP

Product Name	17" Capacitive Touch Screen Monitor
Model Number	ZL17TMBCAP
IP rating	IP65 Front / IP40 Back
Active Display	33.79(H) × 27.04(W)cm
Aspect ratio	5:4
Physical resolution	1280 × 768
Brightness	300(cd/m ²)
Contrast	1000:1
Backlight Lifetime (hours)	LED/30,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL185TMBCAP

Product Name	18.5" Capacitive Touch Screen Monitor
Model Number	ZL185TMBCAP
IP rating	IP65 Front / IP40 Back
Active Display	41.08(H) × 23.14(W)cm
Aspect ratio	16:9
Physical resolution	1920 x 1080
Brightness	300(cd/m ²)
Contrast	1000:1
Backlight Lifetime (hours)	LED/15,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL19TMBCAP

Product Name	19" Capacitive Touch Screen Monitor
Model Number	ZL19TMBCAP
IP rating	IP65 Front / IP40 Back
Active Display	40.92(H) × 25.61(W)cm
Aspect ratio	5:4
Physical resolution	1280 × 1024
Brightness	300(cd/m ²)
Contrast	1000:1
Backlight Lifetime (hours)	LED/15,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In

Industrial Touch Screen Monitor



ZL215TMBCAP

Product Name	21.5" Capacitive Touch Screen Monitor
Model Number	ZL215TMBCAP
IP rating	IP65 Front / IP40 Back
Active Display	47.76(H) × 26.91(W)cm
Aspect ratio	16:9
Physical resolution	1920×1080
Brightness	350(cd/m ²)
Contrast	1000:1
Backlight Lifetime (hours)	LED/40,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL24TMBCAP

Product Name	24" Capacitive Touch Screen Monitor
Model Number	ZL24TMBCAP
IP rating	IP65 Front / IP40 Back
Active Display	52.21(H) × 29.44(W)cm
Aspect ratio	16:9
Physical resolution	1920 × 1080
Brightness	350(cd/m ²)
Contrast	1000:1
Backlight Lifetime (hours)	LED/20,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL24TMBCAP-P

Product Name	24" Capacitive Touch Screen Monitor
Model Number	ZL24TMBCAP-P
IP rating	IP65 Front / IP40 Back
Active Display	52.21(H) × 29.44(W)cm
Aspect ratio	16:9
Physical resolution	1920 × 1080
Brightness	350(cd/m ²)
Contrast	1000:1
Backlight Lifetime (hours)	LED/20,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL27TMBCAP

Product Name	27" Capacitive Touch Screen Monitor
Model Number	ZL27TMBCAP
IP rating	IP65 Front / IP40 Back
Active Display	59.86(H) × 33.71(W)cm
Aspect ratio	16:9
Physical resolution	1920 × 1080
Brightness	350(cd/m ²)
Contrast	3000:1
Backlight Lifetime (hours)	LED/30,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL32TMBCAP

Product Name	32" Capacitive Touch Screen Monitor
Model Number	ZL32TMBCAP
IP rating	IP65 Front / IP40 Back
Active Display	69.84(H) × 39.29(W)cm
Aspect ratio	16:9
Physical resolution	1920 × 1080
Brightness	350(cd/m ²)
Contrast	3000:1
Backlight Lifetime (hours)	LED/30,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL430TMBCAP

Product Name	43" Capacitive Touch Screen Monitor
Model Number	ZL430TMBCAP
IP rating	IP65 Front / IP40 Back
Active Display	94.09(H) × 52.92(W)cm
Aspect ratio	16:9
Physical resolution	1920 × 1080
Brightness	400(cd/m ²)
Contrast	3000:1
Backlight Lifetime (hours)	LED/60,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In

Open Frame Touch Screen Monitor

Our open frame touch screen monitors is designed to meet your needs. These monitors are ideal for industrial and business applications, boasting a responsive capacitive 10-finger multitouch panel. Built for reliability, they feature A+ quality LCD display panels with energy-efficient backlight LED technology.




Standard Sizes 7" – 55"

Open Frame Touch Screen Monitor




ZL07TMBCAP-OF	
Product Name	7" Open Frame Capacitive Touch Screen Monitor
Model Number	ZL07TMBCAP-OF
IP rating	IP65 Front / IP40 Back
Active Display	15.42(H) × 8.59(W)cm
Aspect ratio	16:9
Physical resolution	1024 × 600
Brightness	300(cd/m ²)
Contrast	800:1
Backlight Lifetime (hours)	100000 (hours)
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (Inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL97TMBCAP-OF	
Product Name	10" Open Frame Capacitive Touch Screen Monitor
Model Number	ZL97TMBCAP-OF
IP rating	IP65 Front / IP40 Back
Active Display	19.65(H) × 14.80(W)cm
Aspect ratio	4:3
Physical resolution	1024 × 768
Brightness	300(cd/m ²)
Contrast	800:1
Backlight Lifetime (hours)	LED/20,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (Inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL116TMBCAP-OF	
Product Name	11.6" Open Frame Capacitive Touch Screen Monitor
Model Number	ZL116TMBCAP-OF
IP rating	IP65 Front / IP40 Back
Active Display	25.63(H) × 14.42(W)cm
Aspect ratio	16:9
Physical resolution	1920 × 1080
Brightness	300(cd/m ²)
Contrast	800:1
Backlight Lifetime (hours)	100,000 (hours)
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (Inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL12TMBCAP-OF	
Product Name	12" Open Frame Capacitive Touch Screen Monitor
Model Number	ZL12TMBCAP-OF
IP rating	IP65 Front / IP40 Back
Active Display	24.61(H) × 18.44(W)cm
Aspect ratio	4:3
Physical resolution	1024 × 768
Brightness	300(cd/m ²)
Contrast	1500:1
Backlight Lifetime (hours)	50,000 (hours)
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (Inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL15TMBCAP-OF	
Product Name	15" Open Frame Capacitive Touch Screen Monitor
Model Number	ZL15TMBCAP-OF
IP rating	IP65 Front / IP40 Back
Active Display	30.4(H) × 22.8(W)cm
Aspect ratio	4:3
Physical resolution	1024×768
Brightness	350(cd/m ²)
Contrast	700:1
Backlight Lifetime (hours)	100,000 (hours)
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (Inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL156TMBCAP-OF	
Product Name	15.6" Open Frame Capacitive Touch Screen Monitor
Model Number	ZL156TMBCAP-OF
IP rating	IP65 Front / IP40 Back
Active Display	34.42(H) × 19.36(W)cm
Aspect ratio	16:9
Physical resolution	1920 × 1080
Brightness	350(cd/m ²)
Contrast	800:1
Backlight Lifetime (hours)	30,000 (hours)
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (Inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In

Open Frame Touch Screen Monitor




ZL17TMBCAP-OF	
Product Name	17" Open Frame Capacitive Touch Screen Monitor
Model Number	ZL17TMBCAP-OF
IP rating	IP65 Front / IP40 Back
Active Display	14.50(H) × 12.06(W)cm
Aspect ratio	5:4
Physical resolution	1280 × 1024
Brightness	300(cd/m ²)
Contrast	1000:1
Backlight Lifetime (hours)	30,000 (hours)
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (Inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL215TMBCAP-OF	
Product Name	21.5" Open Frame Capacitive Touch Screen Monitor
Model Number	ZL215TMBCAP-OF
IP rating	IP65 Front / IP40 Back
Active Display	47.70(H) × 26.80(W)cm
Aspect ratio	16:9
Physical resolution	1920 × 1080
Brightness	350(cd/m ²)
Contrast	1000:1
Backlight Lifetime (hours)	100,000 (hours)
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (Inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In




ZL27TMBCAP-OF	
Product Name	27" Open Frame Capacitive Touch Screen Monitor
Model Number	ZL27TMBCAP-OF
IP rating	IP65 Front / IP40 Back
Active Display	59.86(H) × 33.71(W)cm
Aspect ratio	16:9
Physical resolution	1920 × 1080
Brightness	350(cd/m ²)
Contrast	3000:1
Backlight Lifetime (hours)	LED/30,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (Inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL32TMBCAP-OF	
Product Name	32" Open Frame Capacitive Touch Screen Monitor
Model Number	ZL32TMBCAP-OF
IP rating	IP65 Front / IP40 Back
Active Display	69.84(H) × 39.29(W)cm
Aspect ratio	16:9
Physical resolution	1920×1080
Brightness	350(cd/m ²)
Contrast	3000:1
Backlight Lifetime (hours)	100,000 (hours)
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (Inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL43TMBCAP-OF	
Product Name	43" Open Frame Capacitive Touch Screen Monitor
Model Number	ZL43TMBCAP-OF
IP rating	IP65 Front / IP40 Back
Active Display	94.09(H) × 52.92(W)cm
Aspect ratio	16:9
Physical resolution	1920×1080
Brightness	400(cd/m ²)
Contrast	3000:1
Backlight Lifetime (hours)	100,000 (hours)
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (Inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In



ZL55TMBCAP-OF	
Product Name	55" Open Frame Capacitive Touch Screen Monitor
Model Number	ZL55TMBCAP-OF
IP rating	IP65 Front / IP40 Back
Active Display	121.00(H) × 68.00(W)cm
Aspect ratio	16:9
Physical resolution	1920 × 1080
Brightness	500(cd/m ²)
Contrast	1400:1
Backlight Lifetime (hours)	LED/50,000
Touch Panel Drivers	Windows; Linux; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Operating Temp	-10 °C ~ 65 °C 10% to 90% Humidity
Power Supply	12V DC, 3A
External Connectors	1 × HDMI 1.3 (Inch.HDCP); 1 × DP; 1 × VGA 1 × PC-Audio; 1 × USB; 1 × 12V DC-In

Slot Machine

Slot Machine Touch Screen Monitors For Casino And Gaming


Modernize your casino gaming experience with our cutting-edge slot machine screens. Our monitors are specifically designed with Edge LED Lights and feature 10 Points Capacitive Touch Screen technology, providing an immersive and interactive gameplay environment.



Slot Machine Touch Screen Monitors



ZLF24LTM	
Product Name	23.8" Inch Slot Machine Touch Screen Monitor
Model Number	ZLF24LTM
Active Display	52.70(H) × 29.64(W)cm
Aspect ratio	16:9
Physical resolution	1920×1080
Brightness	350(cd/m ²)
Contrast	1000:1
Backlight Lifetime (hours)	LED/50,000
Touch Panel Drivers	Windows; Linux; Android
Touch Technology	Projected Capacitive (PCAP)
LED Frame	Front, RGB, 12V
Touch/Non-Touch Type	Printed 3mm Tempered Glass
Touch Point	10
Power Supply	12V DC, 3A
Video Interface	VGA + DVI standard, HDMI and DisplayPort available




ZLF27LTM	
Product Name	27" Inch Slot Machine Touch Screen Monitor
Model Number	ZLF27LTM
Active Display	59.78(H) × 33.63(W)cm
Aspect ratio	16:9
Physical resolution	1920×1080
Brightness	350(cd/m ²)
Contrast	1000:1
Backlight Lifetime (hours)	LED/50,000
Touch Panel Drivers	Windows; Linux; Android
Touch Technology	Projected Capacitive (PCAP)
LED Frame	Front, RGB, 12V
Touch/Non-Touch Type	Printed 3mm Tempered Glass
Touch Point	10
Power Supply	12V DC, 3A
Video Interface	VGA + DVI standard, HDMI and DisplayPort available




Edge LED Light Bar Touch Screen Monitors for Slot Machine

Enhance your gaming experience with our high-brightness LED light bar touch screen monitors. Featuring 10-point capacitive touch screens, these monitors deliver a seamless and thrilling gaming experience. Choose from a range of sizes including 23.8", 27", 32", and 43" with HD, FHD, and 4K resolution options.



ZLF32LTM	
Product Name	32" Inch Slot Machine Touch Screen Monitor
Model Number	ZLF32LTM
Active Display	69.84(H) × 39.28(W)cm
Aspect ratio	16:9
Physical resolution	1920×1080
Brightness	400(cd/m ²)
Contrast	1200:1
Backlight Lifetime (hours)	LED/50,000
Touch Panel Drivers	Windows; Linux; Android
Touch Technology	Projected Capacitive (PCAP)
LED Frame	Front, RGB, 12V
Touch/Non-Touch Type	Printed 3mm Tempered Glass
Touch Point	10
Power Supply	12V DC, 3A
Video Interface	VGA + DVI standard, HDMI and DisplayPort available



ZLF43LTM	
Product Name	43" Inch Slot Machine Touch Screen Monitor
Model Number	ZLF43LTM
Active Display	94.11(H) × 52.94(W)cm
Aspect ratio	16:9
Physical resolution	1920×1080
Brightness	500(cd/m ²)
Contrast	1200:1
Backlight Lifetime (hours)	LED/50,000
Touch Panel Drivers	Windows; Linux; Android
Touch Technology	Projected Capacitive (PCAP)
LED Frame	Front, RGB, 12V
Touch/Non-Touch Type	Printed 3mm Tempered Glass
Touch Point	10
Power Supply	12V DC, 3A
Video Interface	VGA + DVI standard, HDMI and DisplayPort available

Industrial Panel Pcs

High-Performance Industrial Panel PCs for Demanding Environments

Our high-performance industrial panel PCs are rugged, reliable, and fanless designed for long-term operations (24/7), even in the most challenging conditions. These panel PCs feature a 10 Points PCAP Touch screen and a true-flat design for easy installation in any application, like factory automation, self-service kiosks, and smart lockers.



Industrial Panel Pcs




ZL07PC-C	
Product Name	7" Industrial Panel PC
Model Number	ZL07PC-C
IP rating	IP65 Front / IP40 Back
Active Display	15.36(H) × 9.00(W)cm
Aspect ratio	16:9
Physical resolution	1024 × 600
Brightness	300(cd/m ²)
Contrast	700:1
Backlight Lifetime (hours)	LED / 20,000
Touch Life (Contacts)	Unlimited
Touch Panel Drivers	Windows; Linux; Android
CPU	Intel® Core I3-3217U
Memory	4GB
Storage	Zuljana Industrial 64GB SSD
External Connectors:	
1 x 12V DC-In; 2 x USB 3.0; 2x USB 2.0; 1 x HDMI; 1 x MIC-In & EAR-Out; 1 x DP; 3 x COM port Full-PIN - RS232/485; 5V/12V; 2 x 10/100/1000Mbit RJ45 Ports	



ZL08PC-C	
Product Name	8" Industrial Panel PC
Model Number	ZL08PC-C
IP rating	IP65 Front / IP40 Back
Active Display	16.3(H) × 12.25(W)cm
Aspect ratio	4:3
Physical resolution	1024 × 768
Brightness	300(cd/m ²)
Contrast	700:1
Backlight Lifetime (hours)	LED / 20,000
Touch Life (Contacts)	Unlimited
Touch Panel Drivers	Windows; Linux; Android
CPU	Intel® Core I3-3217U
Memory	4GB
Storage	Zuljana Industrial 64GB SSD
External Connectors:	
1 x 12V DC-In; 2 x USB 3.0; 2x USB 2.0; 1 x HDMI; 1 x MIC-In & EAR-Out; 1 x DP; 3 x COM port Full-PIN - RS232/485; 5V/12V; 2 x 10/100/1000Mbit RJ45 Ports	

Touch Screen Monitor


Mobile computers help businesses maximize operational efficiency and customer satisfaction by enabling employees to line-bust, manage inventory and fulfill mobile orders. manage inventory and fulfill mobile orders.



ZL97PC-C	
Product Name	10" Industrial Panel PC
Model Number	ZL97PC-C
IP rating	IP65 Front / IP40 Back
Active Display	19.65(H) × 14.80(W)cm
Aspect ratio	4:3
Physical resolution	1024 × 768
Brightness	300(cd/m ²)
Contrast	800:1
Backlight Lifetime (hours)	LED / 20,000
Touch Life (Contacts)	Unlimited
Touch Panel Drivers	Windows; Linux; Android
CPU	Intel® Core I3-3217U
Memory	4GB
Storage	Zuljana Industrial 64GB SSD
External Connectors:	
1 x 12V DC-In; 2 x USB 3.0; 2x USB 2.0; 1 x HDMI; 1 x MIC-In & EAR-Out; 1 x DP; 3 x COM port Full-PIN - RS232/485; 5V/12V; 2 x 10/100/1000Mbit RJ45 Ports	



ZL101PC-C	
Product Name	10.1" Industrial Panel PC
Model Number	ZL101PC-C
IP rating	IP65 Front / IP40 Back
Active Display	21.80(H) × 21.80(W)cm
Aspect ratio	16:10
Physical resolution	1280 × 800
Brightness	300(cd/m ²)
Contrast	700:1
Backlight Lifetime (hours)	LED / 20,000
Touch Life (Contacts)	Unlimited
Touch Panel Drivers	Windows; Linux; Android
CPU	Intel® Core I3-3217U
Memory	4GB
Storage	Zuljana Industrial 64GB SSD
External Connectors:	
1 x 12V DC-In; 2 x USB 3.0; 2x USB 2.0; 1 x HDMI; 1 x MIC-In & EAR-Out; 1 x DP; 3 x COM port Full-PIN - RS232/485; 5V/12V; 2 x 10/100/1000Mbit RJ45 Ports	



ZL121PC-C	
Product Name	12.1" Industrial Panel PC
Model Number	ZL121PC-C
IP rating	IP65 Front / IP40 Back
Active Display	24.60(H) × 18.40(W)cm
Aspect ratio	4:3
Physical resolution	1024 × 768
Brightness	300(cd/m ²)
Contrast	700:1
Backlight Lifetime (hours)	LED / 20,000
Touch Life (Contacts)	Unlimited
Touch Panel Drivers	Windows; Linux; Android
CPU	Intel® Core I3-3217U
Memory	4GB
Storage	Zuljana Industrial 64GB SSD
External Connectors:	
1 x 12V DC-In; 2 x USB 3.0; 2x USB 2.0; 1 x HDMI; 1 x MIC-In & EAR-Out; 1 x DP; 3 x COM port Full-PIN - RS232/485; 5V/12V; 2 x 10/100/1000Mbit RJ45 Ports	

Industrial Panel Pcs



ZL15PC-C	
Product Name	15" Industrial Panel PC
Model Number	ZL15PC-C
IP rating	IP65 Front / IP40 Back
Active Display	30.40(H) × 30.40(W)cm
Aspect ratio	4:3
Physical resolution	1024 × 768
Brightness	300(cd/m ²)
Contrast	700:1
Backlight Lifetime (hours)	LED/30,000
Touch Life (Contacts)	Unlimited
Touch Panel Drivers	Windows; Linux; Android
CPU	Intel® Core I3-3217U
Memory	4GB
Storage	Zuljana Industrial 64GB SSD
External Connectors:	
1 x 12V DC-In; 2 x USB 3.0; 2x USB 2.0; 1 x HDMI; 1 x MIC-In & EAR-Out; 1 x DP; 3 x COM port Full-PIN - RS232/485; 5V/12V; 2 x 10/100/1000Mbit RJ45 Ports	



ZL156PC-C	
Product Name	15.6" Industrial Panel PC
Model Number	ZL156PC-C
IP rating	IP65 Front / IP40 Back
Active Display	34.53(H) × 19.46(W)cm
Aspect ratio	16:9
Physical resolution	1920 × 1080
Brightness	300(cd/m ²)
Contrast	800:1
Backlight Lifetime (hours)	LED/15,000
Touch Life (Contacts)	Unlimited
Touch Panel Drivers	Windows; Linux; Android
CPU	Intel® Core I3-3217U
Memory	4GB
Storage	Zuljana Industrial 64GB SSD
External Connectors:	
1 x 12V DC-In; 2 x USB 3.0; 2x USB 2.0; 1 x HDMI; 1 x MIC-In & EAR-Out; 1 x DP; 3 x COM port Full-PIN - RS232/485; 5V/12V; 2 x 10/100/1000Mbit RJ45 Ports	

10 Points Responsive Multi Touch Technology

Mobile computers help businesses maximize operational efficiency and customer satisfaction by enabling employees to line-bust, manage inventory and fulfill mobile orders. manage inventory and fulfill mobile orders.



ZL170PC-C	
Product Name	17" Industrial Panel PC
Model Number	ZL170PC-C
IP rating	IP65 Front / IP40 Back
Active Display	33.79(H) × 27.04(W)cm
Aspect ratio	5:4
Physical resolution	1280 × 768
Brightness	300(cd/m ²)
Contrast	1000:1
Backlight Lifetime (hours)	LED/30,000
Touch Life (Contacts)	Unlimited
Touch Panel Drivers	Windows; Linux; Android
CPU	Intel® Core I3-3217U
Memory	4GB
Storage	Zuljana Industrial 64GB SSD
External Connectors:	
1 x 12V DC-In; 2 x USB 3.0; 2x USB 2.0; 1 x HDMI; 1 x MIC-In & EAR-Out; 1 x DP; 3 x COM port Full-PIN - RS232/485; 5V/12V; 2 x 10/100/1000Mbit RJ45 Ports	



ZL185PC-C	
Product Name	18.5" Industrial Panel PC
Model Number	ZL185PC-C
IP rating	IP65 Front / IP40 Back
Active Display	41.08(H) × 23.1(W)cm
Aspect ratio	16:9
Physical resolution	1920 × 1080
Brightness	350(cd/m ²)
Contrast	1000:1
Backlight Lifetime (hours)	LED/15,000
Touch Life (Contacts)	Unlimited
Touch Panel Drivers	Windows; Linux; Android
CPU	Intel® Core I3-3217U
Memory	4GB
Storage	Zuljana Industrial 64GB SSD
External Connectors:	
1 x 12V DC-In; 2 x USB 3.0; 2x USB 2.0; 1 x HDMI; 1 x MIC-In & EAR-Out; 1 x DP; 3 x COM port Full-PIN - RS232/485; 5V/12V; 2 x 10/100/1000Mbit RJ45 Ports	



ZL19PC-C	
Product Name	19" Industrial Panel PC
Model Number	ZL19PC-C
IP rating	IP65 Front / IP40 Back
Active Display	40.92(H) × 25.61(W)cm
Aspect ratio	5:4
Physical resolution	1280 × 1024
Brightness	350(cd/m ²)
Contrast	1000:1
Backlight Lifetime (hours)	LED/15,000
Touch Life (Contacts)	Unlimited
Touch Panel Drivers	Windows; Linux; Android
CPU	Intel® Core I3-3217U
Memory	4GB
Storage	Zuljana Industrial 64GB SSD
External Connectors:	
1 x 12V DC-In; 2 x USB 3.0; 2x USB 2.0; 1 x HDMI; 1 x MIC-In & EAR-Out; 1 x DP; 3 x COM port Full-PIN - RS232/485; 5V/12V; 2 x 10/100/1000Mbit RJ45 Ports	

Industrial Panel Pcs



ZL215PC-C	
Product Name	21.5" Industrial Panel PC
Model Number	ZL215PC-C
IP rating	IP65 Front / IP40 Back
Active Display	47.76(H) × 26.91(W)cm
Aspect ratio	16:9
Physical resolution	1920 × 1080
Brightness	350(cd/m ²)
Contrast	1000:1
Backlight Lifetime (hours)	LED/40,000
Touch Life (Contacts)	Unlimited
Touch Panel Drivers	Windows; Linux; Android
CPU	Intel® Core I3-3217U
Memory	4GB
Storage	Zuljana Industrial 64GB SSD
External Connectors:	
1 x 12V DC-In; 2 x USB 3.0; 2x USB 2.0; 1 x HDMI; 1 x MIC-In & EAR-Out; 1 x DP; 3 x COM port Full-PIN - RS232/485; 5V/12V; 2 x 10/100/1000Mbit RJ45 Ports	



ZL24AIOTSC	
Product Name	24" Industrial Panel PC
Model Number	ZL24AIOTSC
IP rating	IP65 Front / IP40 Back
Active Display	52.21(H) × 29.44(W)cm
Aspect ratio	16:9
Physical resolution	1920 × 1080
Brightness	350(cd/m ²)
Contrast	1000:1
Backlight Lifetime (hours)	LED/20,000
Touch Life (Contacts)	Unlimited
Touch Panel Drivers	Windows; Linux; Android
CPU	Intel® Core I3-3217U
Memory	4GB
Storage	Zuljana Industrial 64GB SSD
External Connectors:	
1 x 12V DC-In; 2 x USB 3.0; 2x USB 2.0; 1 x HDMI; 1 x MIC-In & EAR-Out; 1 x DP; 3 x COM port Full-PIN - RS232/485; 5V/12V; 2 x 10/100/1000Mbit RJ45 Ports	




IP65 Waterproof Touch Panel

Our All-in-One Panel PCs feature an IP65 waterproof touch panel, making them perfect for operations in wet or humid environments. In addition, they have an IP40 rating, which protects them from dust and prevents insects from getting inside.




ZL270PC-C	
Product Name	27" Industrial Panel PC
Model Number	ZL270PC-C
IP rating	IP65 Front / IP40 Back
Active Display	59.86(H) × 33.71(W)cm
Aspect ratio	16:9
Physical resolution	1920 × 1080
Brightness	350(cd/m ²)
Contrast	3000:1
Backlight Lifetime (hours)	LED/30,000
Touch Life (Contacts)	Unlimited
Touch Panel Drivers	Windows; Linux; Android
CPU	Intel® Core I3-3217U
Memory	4GB
Storage	Zuljana Industrial 64GB SSD
External Connectors:	
1 x 12V DC-In; 2 x USB 3.0; 2x USB 2.0; 1 x HDMI; 1 x MIC-In & EAR-Out; 1 x DP; 3 x COM port Full-PIN - RS232/485; 5V/12V; 2 x 10/100/1000Mbit RJ45 Ports	



ZL320PC-C	
Product Name	32" Industrial Panel PC
Model Number	ZL320PC-C
IP rating	IP65 Front / IP40 Back
Active Display	69.84(H) × 39.29(W)cm
Aspect ratio	16:9
Physical resolution	1920 × 1080
Brightness	350(cd/m ²)
Contrast	3000:1
Backlight Lifetime (hours)	LED/30,000
Touch Life (Contacts)	Unlimited
Touch Panel Drivers	Windows; Linux; Android
CPU	Intel® Core I3-3217U
Memory	4GB
Storage	Zuljana Industrial 64GB SSD
External Connectors:	
1 x 12V DC-In; 2 x USB 3.0; 2x USB 2.0; 1 x HDMI; 1 x MIC-In & EAR-Out; 1 x DP; 3 x COM port Full-PIN - RS232/485; 5V/12V; 2 x 10/100/1000Mbit RJ45 Ports	

Stretched LCD Bar Display

Our stretched bar LCD displays offer unique aspect ratios for various applications. From enhancing retail experience to boosting engagement, these displays are game changers. Contact us today and unlock the potential of your project.



Stretched Bar Lcd Display Monitor



ZL19SBD	
Product Name	19" Stretched Bar LCD
Model Number	ZL19SBD
CPU	RockChip RK 3566
RAM	2GB
Internal memory	16GB
Operating system	Android 11
Resolution	1920 x 360
Active area	49.45 (H) x 11.74(W)cm
Luminance	300 (cd/m ²)
Contrast ratio	1200
WiFi	802.11b/g/n
Ethernet	100M/1000M ethernet
Language	Multi-language
Adapter	12V,3A
External Connectors	USB 2.0; SD/MMC card slot; 3.5mm earphone; RJ45



ZL21SBD	
Product Name	21" Stretched Bar LCD
Model Number	ZL21SBD
CPU	RockChip RK 3566
RAM	2GB
Internal memory	16GB
Operating system	Android 11
Resolution	1920 x 132
Active area	52.94 (H) x 6.3(W)cm
Luminance	300(c d/m ²)
Contrast ratio	1200
WiFi	802.11b/g/n
Ethernet	100M/1000M ethernet
Language	Multi-language
Adapter	12V,3A
External Connectors	USB 2.0; SD/MMC card slot; 3.5mm earphone; RJ45



ZL24SBD	
Product Name	24" Stretched Bar LCD
Model Number	ZL24SBD
CPU	RockChip RK 3566
RAM	2GB
Internal memory	16GB
Operating system	Android 11
Resolution	1920 x 360
Active area	61.57 (H) x 14.01(W)cm
Luminance	300(cd/m ²)
Contrast ratio	1200
WiFi	802.11b/g/n
Ethernet	100M/1000M ethernet
Language	Multi-language
Adapter	12V,3A
External Connectors	USB 2.0; SD/MMC card slot; 3.5mm earphone; RJ45



ZL28SBD	
Product Name	28" Stretched Bar LCD
Model Number	ZL28SBD
CPU	RockChip RK 3566
RAM	2GB
Internal memory	16GB
Operating system	Android 11
Resolution	1920 x 360
Active area	73.51 (H) x 16.81(W)cm
Luminance	500(cd/m ²)
Contrast ratio	1200
WiFi	802.11b/g/n
Ethernet	100M/1000M ethernet
Language	Multi-language
Adapter	12V,4A
External Connectors	USB 2.0; SD/MMC card slot; 3.5mm earphone; RJ45



ZL37SBD	
Product Name	37" Stretched Bar LCD
Model Number	ZL37SBD
CPU	RockChip RK 3566
RAM	2GB
Internal memory	16GB
Operating system	Android 11
Resolution	1920*540
Active area	90.211 (H) x 28.44(W)cm
Luminance	500(cd/m ²)
Contrast ratio	4000
WiFi	802.11b/g/n
Ethernet	100M/1000M ethernet
Language	Multi-language
Adapter	Adapter,12V,4A
External Connectors	USB 2.0; SD/MMC card slot; 3.5mm earphone; RJ45



ZL48SBD	
Product Name	48" Stretched Bar LCD
Model Number	ZL48SBD
CPU	RockChip RK 3566
RAM	2GB
Internal memory	16GB
Operating system	Android 11
Resolution	3840*720(4k)
Active area	121.785 (H) x 24.818(W)cm
Luminance	500(cd/m ²)
Contrast ratio	4000
WiFi	802.11b/g/n
Ethernet	100M/1000M ethernet
Language	Multi-language
Adapter	Adapter,12V,4A
External Connectors	USB 2.0; SD/MMC card slot; 3.5mm earphone; RJ45



After Sales Service
Hungary



Sales & Marketing
Pakistan




Manufacturing Plant
China

Shenzhen BaoBao Industrial Co., Ltd **(Dongguan Branch)**

Floor 4, Building 2, Guancheng Sanliang Industrial Park, No. 2,
Chenxing Road, Huangjiang Town, Dongguan City, Guangdong, P.R.C
Postal Code: 523516

 +86 769 81009070

 +86 769 81009071

 enquiry@baobao-industries.com

 www.baobao-industries.com