

# 10.1" Industrial Touch Screen Monitor

ZL101TMBCAP



IP65 Front  
IP40 Back



1280×800



Tempered  
Glass



700:1



400 Nits  
(Optional)



## 10.1 inch Industrial Touch Screen Monitor

Our 10.1 inch touch screen monitor (Model No: ZL101TMBCAP) comes with 10-point multitouch technology, anti-glare treatment, and VESA mounting for easy use. The best part is that our 10.1-inch monitor comes with a high-quality display with 1280 x 800 resolution, an anti-glare surface and a durable aluminum case with IP65 resistance.



Sales & Marketing Office



Production & Assembling



European RMA Office

## Technical Specification

|                                               |                                         |                                   |                                          |
|-----------------------------------------------|-----------------------------------------|-----------------------------------|------------------------------------------|
| <b>Product Name</b>                           | 10.1" Industrial Touch Screen Monitor   | <b>Touch Technology</b>           | Projected Capacitive 10-point Multitouch |
| <b>Model Number</b>                           | ZL101TMBCAP                             | <b>Touch Panel Drivers</b>        | Windows; Linux; Mac; Android             |
| <b>IP Rating</b>                              | IP65 Front / IP40 Back                  | <b>Touch Life (Contacts)</b>      | Unlimited                                |
| <b>Screen Diagonal (Inch/cm)</b>              | 10.1/25.53                              | <b>Surface Hardness</b>           | 7H                                       |
| <b>Active Display Area(cm)</b>                | 21.64(W) x 13.54(H)                     | <b>Surface Treatment</b>          | Anti-Glare (Optional)                    |
| <b>Aspect Ratio</b>                           | 16:10                                   | <b>Glass Strengthening</b>        | Tempered Glass                           |
| <b>Physical Resolution</b>                    | 1280 x 800                              | <b>Operating Temperature (°C)</b> | -10 ~ +60                                |
| <b>Maximum showable resolution</b>            | 1920 x 1080                             | <b>Humidity Range (RH)</b>        | 10% - 90%                                |
| <b>Colours Displayed</b>                      | 16.7M                                   | <b>Net Weight (Kg)</b>            | 1.10                                     |
| <b>Brightness (cd/m2)</b>                     | 400 Nits                                | <b>Gross Weight (Kg)</b>          | 2.30 (Incl.cartonage)                    |
| <b>Contrast</b>                               | 700:1                                   | <b>Housing Material</b>           | Aluminum front/back case                 |
| <b>Typical Reaction Time Tr/ Tf (ms)</b>      | 10/15                                   | <b>Housing(mm)W x H x D</b>       | 259.0 x 178.0 x 32.0                     |
| <b>Visual Angle Horizontal / vertical (°)</b> | 150/145                                 | <b>Mounting</b>                   | VESA 75                                  |
| <b>Backlight/Backlight Lifetime (hours)</b>   | LED/20,000                              | <b>Power Indicator</b>            | Green LED                                |
| <b>External Connectors</b>                    | HDMI, DP, VGA, PC-Audio, USB, 12V DC-IN | <b>Power Supply</b>               | 12V DC, 3A                               |

