

# 27" Outdoor Open Frame Touch Screen Monitor

ZL27TMBCAP-OD



IP65 Front  
IP40 Back



1920 x 1080



Tempered  
Glass



1000:1



1000 Nits  
(Optional)



## 27 inch Outdoor Open Frame Touch Screen Monitor

Our 27 inch outdoor open frame touch screen monitor (Model No: ZL27TMBCAP-OD) comes with 10-point multitouch technology, anti-glare treatment, and VESA mounting for easy use. The best part is that our 27-inch monitor comes with a high-quality display with 1920 x 1080 resolution, an anti-glare surface and a durable aluminum case with IP65 resistance.



Sales & Marketing Office



Production & Assembling



European RMA Office

## Technical Specification

|                                               |                                            |                                   |                                          |
|-----------------------------------------------|--------------------------------------------|-----------------------------------|------------------------------------------|
| <b>Product Name</b>                           | 27"Outdoor Touch Screen Monitor            | <b>Touch Technology</b>           | Projected Capacitive 10-point Multitouch |
| <b>Model Number</b>                           | ZL27TMCAP-OD                               | <b>Touch Panel Drivers</b>        | Windows; Linux; Mac; Android             |
| <b>IP Rating</b>                              | IP65 Front / IP40 Back                     | <b>Touch Life (Contacts)</b>      | Unlimited                                |
| <b>Screen Diagonal (Inch/cm)</b>              | 27/68.59                                   | <b>Surface Hardness</b>           | 7H                                       |
| <b>Active Display Area(cm)</b>                | 59.78(H)×33.63(V)                          | <b>Surface Treatment</b>          | Optical Bonding + Anti-Glare             |
| <b>Aspect Ratio</b>                           | 16:9                                       | <b>Glass Strengthening</b>        | Tempered Glass                           |
| <b>Physical Resolution</b>                    | 1920x1080                                  | <b>Operating Temperature (°C)</b> | -10 ~ +60                                |
| <b>Maximum showable resolution</b>            | 1920x1080                                  | <b>Humidity Range (RH)</b>        | 10% - 90%                                |
| <b>Colours Displayed</b>                      | 16.7M                                      | <b>Net Weight (Kg)</b>            | 12                                       |
| <b>Brightness (cd/m2)</b>                     | 1000 Nits                                  | <b>Gross Weight (Kg)</b>          | 14 (Incl.cartonage)                      |
| <b>Contrast</b>                               | 1000:1                                     | <b>Housing Material</b>           | Aluminum front/back case                 |
| <b>Typical Reaction Time Tr/ Tf (ms)</b>      | 7/5                                        | <b>Housing(mm)L x W x H</b>       | 414.97 × 658 × 63.5                      |
| <b>Visual Angle Horizontal / vertical (°)</b> | 178/178                                    | <b>Mounting</b>                   | VESA 100                                 |
| <b>Backlight/Backlight Lifetime (hours)</b>   | LED/30,000                                 | <b>Power Indicator</b>            | Green LED                                |
| <b>External Connectors</b>                    | HDMI, DVI-D, VGA, PC-Audio, USB, 12V DC-IN | <b>Power Supply</b>               | 12V DC-Out                               |

